

DIXON™

SECURITY CAMERAS

phone: 801.455.0413

fax: 213.536.2038

email: dixonsecurity@gmail.com

location: 1744 Segó Lily Drive
Sandy, UT 84092

ED9732NV

NETWORK VIDEO RECORDER

FEATURES:

- Supports 32 CH 3MP@30fps or 1080P@30fps or 960P@30fps or 720P@30fps IP input
- Multi-mode recording: manual / timer / motion / sensor
- Playback : support 16 CH playback
- Search : calendar / time, events (sensor, motion)
- Express and flexible backup via USB, network or DVD-RW (SATA)
- DHCP, DDNS, PPPoE network protocol and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- HDMI 1080P output, true high resolution display
- Supports PTZ preset and auto cruise, up to 128 presets and 8 cruises
- Powerful smart phone surveillance supporting iPhone, Android. Compatible with 3G



SPECIFICATIONS

Video Output	HDMI*1:1080p (1920*1080) / VGA*1:1080p (1920*1080)
Resolution	3mp / 1080p / 960p / 720p
IP input Frame Rate	32ch 3mp / 1080p / 960p / 720p @30fps
Audio Input/Output	32ch input / RCA*1 output
Record Resolution	3mp: 2048x1536 / 1080p: 1920*1080 / 960p: 1280*960 / 720p: 1280*720 / D1: 704*576
fps Frame Rate	960fps(NTSC)
Bit Rate / Encode	256Kbps~12Mbps; VBR/CBR
Quality & Mode	6 Level; Manual, Timer, Motion, Sensor
File Manager	Lock, Unlock, Reserving Time
Playback / Function	16CH / Play, Pause, FF, FB; Digital Zoom
Search	Time/Calendar search, event (motion, external alarm)
Smart Search	Apply different colors to display whether a channel is a period of time is recording or not
Alarm Input/Output	16ch local input, support IPC alarm input; 4ch alarm output
Alarm Mode / Triggering	Sensor, Motion, Video Loss / Record, Alarm out, email, etc
Common Interface	GMAC*1
Protocol	TCP/IP, UDP, DHCP, DNS, PPPoE, DDNS, Email
OS / Function	iPhone, Android / multi-screen surveillance, record, snapshot, PTZ control, save device list
HDD / RS485	SATA X 8 / RS485 X 2, support PTZ and keyboard
USB	USB3.0 x 1, USB2.0 x 1, one for mouse, another for USB backup device
Power Supply	ATX (AC110~240v)
Dimensions	16.9"w x 3.5"h x 11.8"d (430x450x89mm)
Working Environment	14°F ~ 122°F (-10~55°C), 10%~90% humidity