

IP-IR3E42-3.6mm

HD SDI HIGH RESOLUTION CAMERA

FEATURES:

- 1/3" 3MP CMOS Sensor
- Recording: 3MP @15fps
- DWDR, 3DNR, ICR
- 3.6mm Fixed Lens
- 42 IR; Distance: 65-98ft
- ONVIF Version 2.0 Conformance
- DC 12v / PoE; Weatherproof



SPECIFICATIONS

Image Sensor & Pixels	1/3" 2MP CMOS Lens; 2048x1536
Electronic Shutter	1/25s - 1/100,000s
Min. Illumination	0 Lux (IR On)
Lens & Auto Iris	3.6mm Fixed Lens; Fixed Iris
Day/Night	ICR Auto Switch
WDR & DNR	Digital WDR; 3D Noise Reduction
Encode Mode	VCR/CBR
Image Quality	Five levels BVR; Freely Adjustable Under CBR
Bitrate	64kbps - 8mbps
Resolution	3MP (2048x1536), 1080p (1920x1080), 720p (1280x720), D1, CIF, 480x240
Multi-Streams	3MP (1-15fps), 1920x1080 (1-30fps), 1280x720 (1-10fps), D1 (1-30fps), CIF (1-30fps) 480x240 (1-30fps)
Image Settings	Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc.
ROI	Support
Network	RJ45
Remote Monitoring	IE Browsing, CMS Remote Control
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Interface Protocol	ONVIF, GB-T/28181-2011
Storage	Network Remote Storage
Smart Alarm	Motion Alarm
IR Distance	65-98ft (20-30m); 42 IR
Waterproof	IP66
Power Supply	DC 12v / PoE
Power Consumption	< 4W (ICR OFF); < 7W (ICR ON)
Working Environment	-40°F~122°F (-40°C~50°C), 10-90% humidity
Dimension	3.4"x8.6"; 1.3lbs