

PT9200-SDI

HD SDI HIGH RESOLUTION CAMERA

FEATURES:

- Integrated Structure, Convenient and Fast Installation
- Built-in Heater and Radiating System
- Built-in 36 x zoom (3x optical, 12x digital)
- 50%, High Sensitivity Mode, 50% Normal Mode
- Signal System
- 128 Presents
- Park Action Function; Auto-Call Presets/Start-up Tour; Pattern, Scan & Display Areas After Idle Time
- Screen Display Pan/Tilt Position, Zoom, etc.
- IP66 All-Day Defend Cover
- Built-in TVSI 500W Lightning-proof, Surge-proof & Wave-proof
- All-In-One, Highly Compact Camera Ideal For Demanding Applications Such As Video Surveillance, Public Transportation, Sports, Video Conferencing & More



SPECIFICATIONS

CAMERA	Sensor	1/3" Sony Original Zoom Camera
	Scanning System	2:1 Interlacing
	Effective Pixels	Approximately 3.27 Megapixels
	White Balance	Auto, ATW, Indoor, Outdoor, Outdoor Auto, Sodium Vapor Lamp (Fix/Auto), One-Push, Manual
	Back-Compensation	Off / Auto
	Focus	f=3.0mm (wide) ~ 9.0mm (tele) F1.2 to F2.1
	Shutter	1s ~ 1/10,000s
	Manual Speed	Pan (0.5°~160°/s); Tilt (0.5°~90°/s)
	Preset Speed	320°/s
	Rotation	Continuously 360°; Tilt 0°~90° with auto-flip
	Speed Proportion	As the length of Focus, to auto-adjust the speed
	Preset	128 preset, title can be edited
	Auto-Flip	Tilt down 90°; with auto-flip 180°
	Scan	355° Programmable, 4 Scans
	Display Zone	8 Programmable Zones with Titles
	VIDEO	Sync Model
Decoder		Built-in
VIDEO	Video Output	Female BNC
	Remote Controlling	RS 485
ENVIRONMENT	Baud Rate (RS485)	2400 / 4800 / 9600 / 19200 bps
	ID Range	1~254
	Temperature	-22°F~155°F
	Humidity	0~95% (no coden)
	Protection Grade	IP 66, 150W Lightning-proof, Surge-proof, All Day Defend Cover
	Power Supply	AC 24V
ENVIRONMENT	Power Consumption	< 12W