

# DIXON™

## SECURITY CAMERAS

phone: 801.455.0413

fax: 213.536.2038

email: [dixonsecurity@gmail.com](mailto:dixonsecurity@gmail.com)

location: 1744 Segó Lily Drive  
Sandy, UT 84092

### ED9308NV-4P

#### NETWORK VIDEO RECORDER

#### FEATURES:

- Playback: 8ch playback
- Search: calendar, time, events (sensor, motion)
- Support 8ch 3mp / 1080p / 960p / 720p @30fps IP input
- Pentaplex: preview record, playback, backup & remote access
- DHCP, DDNS, PPPoE network protocol and CMS supported
- Remote control via IE or CMS: preview, playback, backup, PTZ & configuration
- Multi-user online simultaneously; dual stream
- HDMI 1080p output, true high resolution display
- Support PTZ preset and auto cruise, up to 128 presets and 8 cruises
- Powerful smart phone surveillance supporting iPhone & Android
- Compatible with 3G phone, backup via USB, Network
- Complete SDK software available, easy to integrate with other applications



#### SPECIFICATIONS

Video Output	HDMI*1:1080p (1920*1080) / VGA*1:1080p (1920*1080)
Resolution	3mp / 1080p / 960p / 720p
IP input Frame Rate	8ch 3mp / 1080p / 960p / 720p @30fps
Audio Input/Output	8ch IPC input / RCA*1
Record Resolution	3mp: 2048x1536 / 1080p: 1920*1080 / 720p: 1280*720 / D1: 704*576
fps Frame Rate	200fps(PAL) 240fps(NTSC)
Bit Rate / Encode	256Kbps~12Mbps; VBR/CBR
Quality & Mode	6 Level; Manual, Timer, Motion, Sensor
File Manager	Lock, Unlock, Reserving Time
Playback / Function	8CH / Play, Pause, FF, FB; Digital Zoom
Search	Time/Calendar search, event (motion, external alarm)
Smart Search	Apply different colors to display whether a channel is a period of time is recording or not
Alarm Input/Output	No local input, support IPC alarm input / No alarm output
Alarm Mode / Triggering	Sensor, Motion, Video Loss / Record, Alarm out, email, etc
Common Interface	GMAC*1
Protocol	TCP/IP, UDP, DHCP, DNS, PPPoE, DDNS, Email
Smart Phone OS	iPhone, Android
HDD / RS485	SATA X 1 / RS485 X 1, support PTZ and keyboard
USB	USB3.0 x 1, USB2.0 x 1, one for mouse, another for USB backup device
Power Supply	DC12v/DC48v; 4xPoE
Dimensions	11.8"w x 10.6"h x 2.3"d (300x270x58mm)
Working Environment	14°F ~ 131°F (-10~55°C), 10%~90% humidity